

## MIKA COLOURFLOW & TUNABLE WHITE



Der Mika ist ein dreh- und schwenkbarer LED-Downlighter, der eine große Auswahl an LED-Lichtquellen und leicht austauschbare Optiken bietet. Schaffen Sie schöne Atmosphären mit der ColourFlow-Technologie. Die Mika hat außerdem einen Neigungswinkel von nicht weniger als 43°, was sie ideal für die Beleuchtung von Objekten und Wänden macht. Sie ist netzdimmbar und verfügt über Dimmoptionen von 1-10 V, DALI, DMX512 und Casambi Bluetooth.

**Kategorien:** [Mika Series](#), [Innenraum](#), [Deckeneinbauleuchten](#), [ColourFlow](#), [Möbelgeschäfte](#), [Hotels und Restaurants](#), [Buros](#), [Shops](#)

### > Specifications

|                    |                                                         |
|--------------------|---------------------------------------------------------|
| Type               | Mika ColourFlow & Tunable White, ColourFlow Downlighter |
| Colour             | Black or White                                          |
| Material           | PC/ABS V0, coated aluminium                             |
| Weight             | 1325 gram                                               |
| Swivel             | 350° horizontal   43° vertical                          |
| Mounting hole      | 18 cm                                                   |
| Installation depth | 23 cm                                                   |

|              |                                            |
|--------------|--------------------------------------------|
| Optics       | 22°   47°   67°                            |
| Light source | CLS Dynamic Colour Chip                    |
| LED colours  | RGB-W   RGB-A<br>1800K-4000K   2700K-5700K |

|                   |                                   |
|-------------------|-----------------------------------|
| Power consumption | Max. 30 Watt                      |
| Drive current     | 700mA                             |
| Driver            | Driver included   Driver external |
| Dimming           | Casambi   DMX512                  |
| Cable length      | 150 cm                            |

|                  |       |
|------------------|-------|
| IP rating        | IP 20 |
| Protection class | 3     |
| Certifications   | CE    |

|              |                 |
|--------------|-----------------|
| Energy label | A               |
| Lifetime     | 50.000 hours    |
| Warranty     | 5 years         |
| Remarks      | 15° inward tilt |

