# JADE ZOOM



Die Jade Zoom ist eine vielseitige und leistungsstarke LED-Leuchte. Mit einem Zoombereich von 9° bis 58° (Bridgelux) oder 11° bis 67° (Xicato) ist es ideal für Museums-, Galerie- oder hochwertige Einzelhandelsbeleuchtung. Das fortschrittliche optische System sorgt für eine gleichmäßige Lichtqualität, während die Auswahl an LED-Lichtquellen eine perfekte Anpassung an den Beleuchtungsplan ermöglicht.

**Kategorien:** Jade Series, Innenraum, Leuchten für Stromschienen, Museen und Galerien

## > Specifications

| | |
|---|---|
| Type | Jade Zoom, 25 or 35 Watt track or surface mounted spot |
| Colour | Black, white or grey |
| Material | Anodized or coated aluminium & PC/ABS V0 |
| Weight | 955 gram |
| Swivel | 340° horizontal \| 350° vertical |


| | |
|---|---|
| Optics | 9°- 58° \| 11°- 67° |
| Light source | Bridgelux or Xicato |
| Light output | 1500 - 2000 lumen |
| CRI | >92 or >97 |
| LED colours | 2700K \| 3000K \| 3500K \| 4000K |

| | |
|---|---|
| Power consumption | Max. 25 - 35 Watt |
| Power supply | 180~264 VAC |
| Driver | Driver included \| Driver internal |
| Dimming | Local dim \| DALI \| Casambi \| DMX512 \| Wireless DMX |
| Connection | Track adapter, Global or Eutrac |


| | |
|---|---|
| IP rating | IP 20 |
| Protection class | 1 |
| Certifications | CE |

| | |
|---|---|
| Lifetime | 50.000h |
| Warranty | 5 years |

| | |
|---|---|
| Accessories | A customizable snoot that can be build up in segments of 2 cm. Rotatable barndoor, Beam shapers and Honeycomb louvre. |
| Remarks | The beam angle can be adjusted from the backside of the fixture. |




Jade C




Jade B

