REVO INGROUND



Mit mehr als 200 verschiedenen möglichen Konfigurationen ist es mit dieser vielseitigen und nachhaltigen Außenleuchte ganz einfach, die perfekte Beleuchtungskonfiguration für Ihren Raum zu finden. Durch die Wechseloptik können Sie den Abstrahlwinkel je nach gewünschtem Effekt individuell anpassen. Dank der Gore-Tex-Membrantechnologie wird Kondensation im Inneren der Halterung verhindert.

Kategorien: Revo Inground Series, Aussenraum, Bodeneinbauleuchten, Architainment, Hotels und Restaurants, Museen und Galerien

> Specifications

Type	Revo Inground, Outdoor Inground
Colour	Black. Cover ring: Stainless steel
Material	Marine grade 316 stainless steel mounting ring & mounting screws. ABS plastic anti corrosion housing. Aluminium die cast housing.
Weight	6950 gram
Swivel	50° vertical
Mounting hole	25,5 cm
Installation depth	35,5 cm
Pressure	15 kg/cm^2
Ambient temperature	-10°C till 40°C

Optics	8° | 12° | 30° | 61° | 80° | 12x46°
Light source	High Power LED
Light output	2000 lumen
CRI	80
LED colours	2200K | 2400K | 2700K | 3000K | 4000K | amber | blue | red | green

Power consumption	Max. 20 Watt
Power supply	200~277 VAC
Driver	Driver included | Driver internal
Dimming	Mains dimmable | Casambi
Connection	Cable with open end
Cable length	200 cm

IK-class	IK10
IP rating	IP 67
Protection class	3
Certifications	CE
Energy label	A

Lifetime	50.000 hours
Warranty	3 years

Remarks	Ventilation gland with Gore-Tex membrane to avoid condensation. Beam direction adjustable thanks to a solid ball joint. 2/3/4 way gel mould set included. Double IP67 protection.

