

OTIS GII



L'Otis GII est un luminaire polyvalent et économe en énergie, parfait pour les salles d'exposition de meubles ou d'autres commerces de vente au détail. Grâce à ses miroirs réglables indépendants, il peut fournir un éclairage précis et uniforme pour trois objets différents. Les modules LED de l'Otis GII offrent une excellente reproduction des couleurs. Les produits sont mis en valeur grâce à des couleurs identiques que s'ils étaient exposés à la lumière du jour.

Catégories : [Otis Series](#), [Intérieur](#), [Appareils Encastrés](#), [Magasins de meubles](#), [Magasins](#)

> Specifications

| | |
|--------------------|---|
| Type | Otis GII, Downlighter |
| Colour | White or black |
| Material | Plastic (PC_ABS V0), Anodized aluminium |
| Weight | 1400 gram |
| Mounting hole | 210~250 mm |
| Installation depth | 153 mm |
| Optics | 19° 30° 50° |
| Light source | High Power LED |
| CRI | 80~95 |
| LED colours | 2500K 2700K 3000K 3500K 4000K |
| Power consumption | Max. 37 - 55 Watt |
| Drive current | 1050mA |
| Driver | Driver included Driver external |
| Dimming | Mains dim 1-10V dim DALI Casambi DMX512 |
| Connection | CLS Smart Connect system |
| Cable length | 150 cm |
| IP rating | IP 20 |
| Protection class | 3 |
| Certifications | CE |

| | |
|----------|-------------------|
| Lifetime | 50.000 hours |
| LB Value | L90B10 at 50.000h |
| Warranty | 5 years |

| | |
|---------|---|
| Remarks | Each mirror optic holds 2 adjustable mirrors. One can easily adjust the beam angle for perfect illumination of all relevant objects in a room. Also usable without mirrors. |
|---------|---|

