



RUBY BRACKET MODULAR





Le Ruby Bracket Modular est une option polyvalente et de haute qualité pour l'éclairage de vos espaces. Ce produit est disponible avec plusieurs modules LED, ce qui vous permet de choisir l'option la plus adaptée à vos besoins. Avec la gradation totalement analogique, la gradation hybride ou la gradation PWM, vous pouvez aisément personnaliser le flux lumineux pour créer l'ambiance parfaite. De plus, les connecteurs d'entrée et de sortie XLR3 rendent la connexion de votre ligne DMX et le contrôle de l'éclairage particulièrement faciles.

Catégories: Série de produits, Ruby Series, Intérieur, Downlights apparents, Architainment, Théâtres et salles de concert

> Specifications

Type Ruby Bracket Modular, Indoor surface mounted

Colour White or black
Material Coated aluminium

Weight 3600 gram

Optics 16° | 49° | 63°
Light source High Power LED
Light output 8500 lumen

CRI 92

LED colours 2700K | 3000K | 4000K

Power consumption Max. 45 - 90 Watt

Power supply 80 ~ 264


Driver included | Driver internal

Dimming DMX512 | DMX Analog dimmable | DMX Hybrid dimmable | PWM dimmable

Connection Power: Neutrik Powercon TRUE. DMX: XLR3.

IP rating IP 20
Protection class 1
Certifications CE
Energy label A

Lifetime 50000 hours





LB Value L90B10 at 50.000h

Warranty 5 years

Accessories Remarks Reflectors in several different beam angles and a Honeycomb louvre Neutrik Powercon TRUE chassis / DMX XLR3 chassis

