

REVO INGROUND COLOURFLOW DMX



Le Revo ColourFlow est une solution idéale pour créer des effets allant des nuances subtiles et des couleurs pastel aux couleurs très saturées. Le Revo est disponible dans de nombreuses configurations, dont RGBW, RGBA et AWB, afin de créer des teintes délicates qui peuvent être difficiles à obtenir avec d'autres systèmes d'éclairage. Avec ce luminaire unique, vous obtenez une balance des blancs précise entre 1800K et 8000K !

Catégories : [Revo Inground Series](#), [Extérieur](#), [Encastrés de sol](#), [ColourFlow](#), [Architainment](#), [Hotels et Restaurants](#), [Musées et galeries d'art](#)

> Specifications

Type	Revo Inground ColourFlow DMX, Outdoor Inground
Colour	Die cast housing + anti corrosion housing: black. Cover ring: stainless steel colour
Material	Marine grade 316 stainless steel mounting ring. Stainless steel 316 mounting screws. ABS plastic anti corrosion housing. Aluminum die cast housing.
Weight	6950 gram
Swivel	50° vertical
Mounting hole	25,5 cm
Installation depth	35,5 cm
Pressure	15 kg/cm ²
Ambient temperature	-10°C till 40°C

Optics	8° 12° 30° 61° 80° 12x46°
Light source	High Power LED
CRI	~80
LED colours	RGB-W 3000K RGB-W 4000K RGB-A AWB

Power consumption	Max. 20 Watt
Power supply	200~277 VAC
Driver	Driver included Driver internal
Dimming	dmx
Connection	Cable with open end
Cable length	200 cm

IK-class	IK10
IP rating	IP 67
Protection class	3
Certifications	CE
Energy label	A

Lifetime	50.000 hours
LB Value	L90B10 at 50.000h
Warranty	3 years

Remarks Ventilation gland with Gore-Tex membrane fitted to avoid moisture and condensation Fitted with a 5 core DMX combi cable
Beam direction adjustable in multiple directions due to solid ball joint Double IP67 protection.

