

REVO INGROUND



Avec plus de 200 configurations différentes possibles, il est facile de trouver la solution d'éclairage adéquate pour votre espace avec ce luminaire extérieur polyvalent et durable. Les optiques interchangeable vous permettent de personnaliser l'angle de faisceau en fonction de l'effet souhaité. Grâce à la technologie Gore-Tex de la membrane, la condensation à l'intérieur du luminaire est évitée.

Catégories : [Revo Inground Series](#), [Extérieur](#), [Encastrés de sol](#), [Architainment](#), [Hotels et Restaurants](#), [Musées et galeries d'art](#)

> Specifications

Type	Revo Inground, Outdoor Inground
Colour	Black. Cover ring: Stainless steel
Material	Marine grade 316 stainless steel mounting ring & mounting screws. ABS plastic anti corrosion housing. Aluminium die cast housing.
Weight	6950 gram
Swivel	50° vertical
Mounting hole	25,5 cm
Installation depth	35,5 cm
Pressure	15 kg/cm ²
Ambient temperature	-10°C till 40°C

Optics	8° 12° 30° 61° 80° 12x46°
Light source	High Power LED
Light output	2000 lumen
CRI	~80
LED colours	2200K 2400K 2700K 3000K 4000K amber blue red green limegreen

Power consumption	Max. 20 Watt
Power supply	200~277 VAC
Driver	Driver included Driver internal
Dimming	mains casambi
Connection	Cable with open end
Cable length	200 cm

IK-class	IK10
IP rating	IP 67
Protection class	3
Certifications	CE
Energy label	A

Lifetime	50.000 hours
LB Value	L90B10 at 50.000h
Warranty	3 years

Remarks Ventilation gland with Gore-Tex membrane to avoid condensation. Beam direction adjustable thanks to a solid ball joint. 2/3/4 way gel mould set included. Double IP67 protection.

