

RUBY SURFACE COLOURFLOW



Maak kennis met de Ruby Surface ColourFlow - een uniek LED-armatuur die eindeloze mogelijkheden biedt voor verlichtingsdesign. Met wit licht van hoge kwaliteit en perfecte kleurmenging is dit armatuur perfect voor een scala aan toepassingen, van concertzalen tot showrooms. De Tunable White LED-modules kunnen worden afgesteld op de gewenste kleurtemperatuur. De directe DMX 512-bediening maakt hem gebruiksvriendelijk, en de duurzame constructie zorgt voor langdurige prestaties.

Categorieën: [Productseries](#), [Ruby Series](#), [Interieur](#), [Opbouwverlichting](#), [ColourFlow](#), [Toepassingen](#), [Architainment](#), [Kerken](#), [Theaters en concertzalen](#)

> Specifications

Type	Ruby Surface ColourFlow, Indoor surface mounted
Colour	Black or white
Material	Powder coated aluminium
Weight	3698 gram

Optics	16° 49° 63°
Light source	CLS Dynamic Colour Chip
LED colours	RGB-W 3000K RGB-W 4000K RGB-A 1800K-4000K 2700K-6500K

Power consumption	Max. 45 - 90 Watt
Power supply	80 ~ 264 VAC
Driver	Driver included Driver internal
Dimming	dmx analog hybrid pwm nfc
Connection	Open end

IP rating	IP 20
Protection class	1
Certifications	CE
Energy label	A

Lifetime	50000 hours
----------	-------------

LB Value L90B10 at 50.000h
Warranty 5 years

Accessories Reflector available in several different beam angles and a honeycomb louvre
Remarks Fitted with a 5 core DMX combi cable

