

## FLORENCE GIII



De Florence GIII is een 3 watt LED downlighter met een superieure lichtopbrengst en een ultra-compacte vormgeving. Zijn zwarte aluminium afwerking en CNC gesneden massief aluminium behuizing maken het de perfecte keuze voor elke toepassing die een optimale warmteafvoer vereist. Een brede waaier van dimmethodes is beschikbaar, waaronder DMX512, DALI en Casambi.

**Categorieën:** [Florence GIII Series](#), [Interieur](#), [Downlighter](#), [Hotels en restaurants](#), [Musea en Galerijen](#), [Kantoren](#)

### > Specifications

|                    |                                     |
|--------------------|-------------------------------------|
| Type               | Florence GIII, Downlighter          |
| Colour             | Black                               |
| Material           | Coated aluminum                     |
| Weight             | 75 gram                             |
| Swivel             | 360° horizontal   50° vertical      |
| Mounting hole      | 5 cm                                |
| Installation depth | 5 cm                                |
| <hr/>              |                                     |
| Optics             | 15°   40°                           |
| Light source       | High Power LED                      |
| Light output       | 200 lumen                           |
| CRI                | 90                                  |
| LED colours        | 2700K   3000K   4000K               |
| <hr/>              |                                     |
| Power consumption  | Max. 3 Watt                         |
| Drive current      | 700mA                               |
| Driver             | Driver excluded   Driver external   |
| Dimming            | mains   1-10   dali   casambi   dmx |
| Connection         | CLS Smart connect system            |
| Cable length       | 100 cm                              |
| <hr/>              |                                     |
| IP rating          | IP 40                               |
| Protection class   | 3                                   |
| Certifications     | CE                                  |

|              |                              |
|--------------|------------------------------|
| Energy label | A                            |
| Lifetime     | 50000 hours                  |
| LB Value     | L90B10 at 50.000h            |
| Warranty     | 5 years                      |
| Remarks      | Extreme compact measurements |

