FOCUS COMPACT SPOT GII





De Focus Compact Spot GII is een 4 Watt zoomarmatuur. Ontworpen voor vitrineverlichting en andere toepassingen waar een ultracompacte armatuur met variabele zoomoptiek nodig is. De Focus Compact Spot GII heeft een zeer nauwkeurig en traploos zoombereik van 13° tot 65°. Bovendien biedt hij een intern 'slot' voor de montage van kleur- en/of correctiefilters. Hij heeft ook een ruime keuze aan accessoires, waaronder snoots, tilt extenders, couplers, en verlengstukken in 10 of 30 cm om de hoogte van de armatuur aan te passen tot 120 cm.

Categorieën: Focus Series, Interieur, Opbouwverlichting, Architainment, Musea en Galerijen

> Specifications

Type	Focus Compact Spot GII, Indoor surface mounted
Colour	White or black
Material	Anodized aluminium
Weight	135 gram
Swivel	350° horizontal | 90° vertical

Optics	13° ~ 65°
Light source	High Power LED
Light output	219 lumen
CRI	95
LED colours	2700K | 3000K | 4000K

Power consumption	Max. 4 Watt
Drive current	700mA
Driver	Driver excluded | Driver external
Dimming	Mains dimmable | 1-10V dimmable | DALI | Casambi | DMX512
Connection	CLS Smart Connect system
Cable length	150 cm

IP rating	IP 20
Protection class	1
Certifications	CE
Energy label	A

Lifetime	50000 hours
Warranty	3 years

Accessories	Snoot, couplers, tilt extenders & extension pipes of 10 & 30 cm
Remarks	Internal slot for correction filters

