

REVO COMPACT INGROUND



De Revo Compact Inground is een configureerbaar en duurzaam verlichtingsarmatuur. Met meer dan 200 verschillende configuraties is dit armatuur aan te passen aan elke behoefte. De verwisselbare lenzen maken het eenvoudig om de lichtinstelling op locatie te veranderen, en de ventilatiedoos met Gore-Tex membraan voorkomt condensvorming. Dit armatuur is ook klaar voor de toekomst; omdat alle onderdelen gemakkelijk verwisselbaar zijn, zal de Revo Compact Inground nooit verouderd zijn.

Categorieën: [Revo Inground Series](#), [Buitenverlichting](#), [Inground](#), [Architainment](#)

> Specifications

Type	Revo Compact Inground, Outdoor Inground
Colour	Die cast housing + anti corrosion housing: black
Material	Marine grade 316 stainless steel mounting ring. Stainless steel 316 mounting screws. ABS plastic anti corrosion housing. Aluminium die cast housing
Weight	2300 gram
Mounting hole	16,6 cm
Installation depth	19,8 cm
Pressure	15 kg/cm ²
Ambient temperature	-10°C till 40°C

Optics	8° 12° 30° 61° 12 x 46°
Light source	High Power LED
Light output	800 lumen
CRI	~80
LED colours	2200K 2700K 3000K 4000K 5000K 6500K amber blue red green limegreen

Power consumption	Max. 10 Watt
Power supply	100 ~ 240 VAC 24 VDC
Driver	Driver included Driver internal
Dimming	dali
Connection	cable with open end
Cable length	200 cm

IK-class	IK10
IP rating	IP 67
Protection class	1
Certifications	CE

LB Value	L90B10 at 50.000h
Warranty	3 years

Remarks Ventilation gland with Gore-Tex membrane fitted to avoid moisture and condensation IP 67 2/3/4 way gel mold set included in the package Double IP67 protection.

