

## REVO INGROUND DMX



De Revo Inground DMX is een hoogwaardig en duurzaam armatuur dat eenvoudig te installeren en te configureren is. Met de IP67 rating is de Revo perfect voor gebruik in elke buitenomgeving. Eenvoudige en nauwkeurige regeling via DMX512 maakt dit armatuur tot een veelzijdige en krachtige verlichtingsoplossing voor elke installatie.

**Categorieën:** [Revo Inground Series](#), [Buitenverlichting](#), [Inground](#), [Architainment](#), [Hotels en restaurants](#), [Musea en Galerijen](#)

### > Specifications

Type	Revo Inground DMX, Outdoor Inground
Colour	Die cast housing + anti corrosion housing: black. Cover ring: stainless steel colour
Material	Marine grade 316 stainless steel mounting ring. Stainless steel 316 mounting screws. ABS plastic anti corrosion housing. Aluminum die cast housing.
Weight	6950 gram
Swivel	50° vertical
Mounting hole	25,5 cm
Installation depth	35,5 cm
Pressure	15 kg/cm <sup>2</sup>
Ambient temperature	-10°C till 40°C

---

Optics	8°   12°   30°   61°   80°   12x46°
Light source	High Power LED
Light output	2000 lumen
CRI	~80
LED colours	2200K   2400K   2700K   3000K   4000K   5000K   6500K   amber   blue   red   green   limegreen

---

Power consumption	Max. 20 Watt
Power supply	200~277 VAC
Driver	Driver included   Driver internal
Dimming	mains   casambi   dmx
Connection	Cable with open end
Cable length	200 cm

---

IK-class	IK10
IP rating	IP 67
Protection class	3
Certifications	CE
Energy label	A

Lifetime	50.000 hours
LB Value	L90B10 at 50.000h
Warranty	3 years

Remarks                      Ventilation gland with Gore-Tex membrane fitted to avoid moisture and condensation Fitted with a 5 core DMX combi cable  
Beam direction adjustable in multiple directions due to solid ball joint Double IP67 protection.

