

REVO INGROUND TUNABLE WHITE DMX



De Revo Inground Tunable White DMX is de perfecte oplossing voor elke buiteninstallatie. Met zijn IP67-classificatie is hij bestand tegen zware omstandigheden en dankzij de uitgebreide configuratiemogelijkheden levert de Revo licht waar u dat het meest nodig hebt, met een grotere precisie dan ooit tevoren! De Tunable White LED-technologie betekent dat u de kleurtemperatuur van de lichtuitstraling kunt aanpassen om elk gewenst effect te creëren, of het nu voor sfeer of functie is.

Categorieën: [Revo Inground Series](#), [Buitenverlichting](#), [Inground](#), [ColourFlow](#), [Architainment](#), [Hotels en restaurants](#), [Musea en Galerijen](#)

> Specifications

Type	Revo Inground Tunable White DMX, Outdoor Inground
Colour	Die cast housing + anti corrosion housing: black. Cover ring: stainless steel colour
Material	Marine grade 316 stainless steel mounting ring. Stainless steel 316 mounting screws. ABS plastic anti corrosion housing. Aluminum die cast housing.
Weight	6950 gram
Swivel	50° vertical
Mounting hole	25,5 cm
Installation depth	35,5 cm
Pressure	15 kg/cm ²
Ambient temperature	-10°C till 40°C

Optics	8° 12° 30° 61° 80° 12x46°
Light source	High Power LED
CRI	>80
LED colours	1800K-3000K 1800K-4000K 2700K-5000K

Power consumption	Max. 20 Watt
Power supply	200~277 VAC
Driver	Driver included Driver internal
Dimming	dmx
Connection	Cable with open end
Cable length	200 cm

IK-class	IK10
IP rating	IP 67
Protection class	3
Certifications	CE
Energy label	A

Lifetime	50.000 hours
LB Value	L90B10 at 50.000h
Warranty	3 years

Remarks Ventilation gland with Gore-Tex membrane fitted to avoid moisture and condensation Fitted with a 5 core DMX combi cable
Beam direction adjustable in multiple directions due to solid ball joint Double IP67 protection.

