

## REVO INGROUND



Met meer dan 200 verschillende mogelijke configuraties is het altijd mogelijk om de perfecte verlichting voor uw buitenruimte te vinden met dit veelzijdige en duurzame armatuur. Met de verwisselbare optieken kunt u de stralingshoek aanpassen naar het gewenste effect. Dankzij de Gore-Tex membraantechnologie wordt condensatie binnenin het armatuur voorkomen.

**Categorieën:** [Revo Inground Series](#), [Buitenverlichting](#), [Inground](#), [Architainment](#), [Hotels en restaurants](#), [Musea en Galerijen](#)

### > Specifications

Type	Revo Inground, Outdoor Inground
Colour	Black. Cover ring: Stainless steel
Material	Marine grade 316 stainless steel mounting ring & mounting screws. ABS plastic anti corrosion housing. Aluminium die cast housing.
Weight	6950 gram
Swivel	50° vertical
Mounting hole	25,5 cm
Installation depth	35,5 cm
Pressure	15 kg/cm <sup>2</sup>
Ambient temperature	-10°C till 40°C

---

Optics	8°   12°   30°   61°   80°   12x46°
Light source	High Power LED
Light output	2000 lumen
CRI	~80
LED colours	2200K   2400K   2700K   3000K   4000K   amber   blue   red   green   limegreen

---

Power consumption	Max. 20 Watt
Power supply	200~277 VAC
Driver	Driver included   Driver internal
Dimming	mains   casambi
Connection	Cable with open end
Cable length	200 cm

---

IK-class	IK10
IP rating	IP 67
Protection class	3
Certifications	CE
Energy label	A

Lifetime	50.000 hours
LB Value	L90B10 at 50.000h
Warranty	3 years

Remarks                      Ventilation gland with Gore-Tex membrane to avoid condensation. Beam direction adjustable thanks to a solid ball joint. 2/3/4 way gel mould set included. Double IP67 protection.

