

## REVO BASIC XL



De Revo Basic XL is een compact, maar krachtig, 40 watt armatuur voor buitenverlichting die perfect is voor een breed scala van toepassingen. CNC gefreesd uit massief aluminium en IP67 beoordeeld voor optimale bescherming tegen de elementen. Met meer dan 800 mogelijke configuraties kan de Revo Basic XL worden aangepast aan uw specifieke behoeften. En met de verwisselbare optieken en de configureerbare dimmogelijkheden kunt u altijd het perfecte resultaat realiseren.

**Categorieën:** [Revo XL Series](#), [Buitenverlichting](#), [Opbouw](#)

### > Specifications

Type	Revo Basic XL, IP67 outdoor surface mounted fixture
Colour	Blank or Black
Material	CNC machined aluminium
Weight	3600 gram
Swivel	360° horizontal   270° vertical
Ambient temperature	-10°C to 40°C

---

Optics	8°   12°   30°   60°   80°   12x46°
Light source	High Power LED
Light output	3200 lumen
CRI	>80
LED colours	2200K   2400K   2700K   3000K   4000K   5000K   6500K   amber   blue   red   green   limegreen

---

Power consumption	Max. 40 Watt
Power supply	100~240 VAC
Driver	Driver included   Driver internal
Dimming	mains   magno   dali
Connection	Cable with open end
Cable length	200 cm

---

IP rating	IP 67
Protection class	3
Certifications	CE

---

Lifetime	50.000 hours
LB Value	L90B10 at 50.000h
Warranty	3 years

---

Accessories	Snoot, ground pin, extension pipe
Remarks	Ventilation gland with Gore-Tex membrane to avoid condensation. Fitted with a 5 core DMX combi cable





