

## REVO BASIC



De Revo Basic is een 20W, IP67-geclassificeerde buitenverlichtingsarmatuur met een massieve CNC-gefreesde aluminium behuizing en configureerbare opties. Dit armatuur is perfect voor gevelverlichting, tuinen, landschappen en andere toepassingen waar een compact armatuur met een hoge output gewenst is. Met verwisselbare optieken en lenzen kan de REVO Basic worden aangepast aan de behoeften van elke toepassing. En dankzij het duurzame ontwerp zal dit armatuur nooit verouderd raken.

**Categorieën:** [Revo Series](#), [Buitenverlichting](#), [Opbouw](#), [Autoshowrooms](#), [Kantoren](#), [Theaters en concertzalen](#)

### > Specifications

Type	Revo Basic, IP67 Outdoor surface fixture
Colour	Blank or black
Material	CNC cut aluminium
Weight	1800 gram
Swivel	360° horizontal   270° vertical
Ambient temperature	-10°C till 40°C

Optics	8°   12°   30°   60°   80°   12 x 46°
Light source	High Power LED
Light output	2000 lumen
CRI	>80
LED colours	1800K   2200K   2400K   2700K   3000K   4000K   5000K   6500K   amber   blue   red   green   limegreen

Power consumption	Max. 20 Watt
Power supply	100~240 VAC
Driver	Driver included   Driver internal
Dimming	DALI
Connection	Cable with open end
Cable length	200 cm

IP rating	IP 67
Protection class	1
Certifications	CE

---

Lifetime	50.000 hours
LB Value	L90B10 at 50.000h
Warranty	3 years

---

Accessories	Shoot, ground pin, extension pipe
Remarks	Ventillation gland with Gote-Tex membrane to avoid condensation

