

REVO BASIC



De Revo Basic is een 20W, IP67-geclassificeerde buitenverlichtingsarmatuur met een massieve CNC-gefreesde aluminium behuizing en configureerbare opties. Dit armatuur is perfect voor gevelverlichting, tuinen, landschappen en andere toepassingen waar een compact armatuur met een hoge output gewenst is. Met verwisselbare optieken en lenzen kan de REVO Basic worden aangepast aan de behoeften van elke toepassing. En dankzij het duurzame ontwerp zal dit armatuur nooit verouderd raken.

Categorieën: [Revo Series](#), [Buitenverlichting](#), [Opbouw](#), [Autoshowrooms](#), [Kantoren](#), [Theaters en concertzalen](#)

> Specifications

Type	Revo Basic, IP67 Outdoor surface fixture
Colour	Blank or black
Material	CNC cut aluminium
Weight	1800 gram
Swivel	360° horizontal 270° vertical
Ambient temperature	-10°C till 40°C

Optics	8° 12° 30° 60° 80° 12 x 46°
Light source	High Power LED
Light output	2000 lumen
CRI	>80
LED colours	1800K 2200K 2400K 2700K 3000K 4000K 5000K 6500K amber blue red green limegreen

Power consumption	Max. 20 Watt
Power supply	100~240 VAC
Driver	Driver included Driver internal
Dimming	dali
Connection	Cable with open end
Cable length	200 cm

IP rating	IP 67
Protection class	1
Certifications	CE

Lifetime	50.000 hours
LB Value	L90B10 at 50.000h
Warranty	3 years

Accessories	Snoot, ground pin, extension pipe
Remarks	Ventillation gland with Gote-Tex membrane to avoid condensation

