

REVO COMPACT BASIC



De Revo Compact Basic is een 10 watt, IP67 opbouwarmatuur dat CNC gefreesd is uit massief aluminium. Dit veelzijdige armatuur kan worden gebruikt voor gevelverlichting, tuinen, landschap, (kunst)objecten, accentverlichting en alle andere toepassingen waar een compact armatuur met een verrassend hoge lichtopbrengst is vereist. Het duurzame ontwerp maakt hem toekomstbestendig; omdat alle onderdelen eenvoudig uitwisselbaar zijn, zal de Revo Compact nooit verouderd raken.

Categorieën: [Revo Series](#), [Buitenverlichting](#), [Opbouw](#)

> Specifications

Type	Revo Compact Basic, IP67 outdoor fixture
Colour	Aluminium or black
Material	Anodized Aluminium
Weight	1300 gram
Swivel	360° horizontal 270° vertical
Ambient temperature	-10°C till 40°C
<hr/>	
Optics	8° 12° 30° 60° 80° 12x46°
Light source	High Power LED
Light output	800 lumen
CRI	>80
LED colours	1800K 2200K 2700K 3000K 4000K 5000K 6500K amber blue red green limegreen
<hr/>	
Power consumption	Max. 10 Watt
Power supply	180~264 VAC 24 VDC
Driver	Driver included Driver internal
Connection	Cable with open end
Cable length	200 cm
<hr/>	
IP rating	IP 67
Protection class	3
Certifications	CE

Lifetime	50.000 hours
LB Value	L90B10 at 50.000h
Warranty	3 years

Accessories	Snoot, ground pin, extension pipe
Remarks	Gore-Tex membrane to avoid condensation

