

RUBY SURFACE COLOURFLOW





Introducing the Ruby Surface ColourFlow – a unique LED fixture that offers endless possibilities for lighting design. With high-quality white light and perfect colour mixing, this fixture is perfect for a range of applications, from concert halls to showrooms. The Tunable White LED modules can be tuned to your desired colour temperature, making it the perfect choice for any space. Direct DMX 512 control makes it easy to use, and the durable construction ensures long-lasting performance.

Categories: <u>Product Series</u>, <u>Ruby Series</u>, <u>Indoor</u>, <u>Surface mounted</u>, <u>ColourFlow</u>, <u>Applications</u>, <u>Architainment</u>, <u>Churches</u>, <u>Theatres & Concert halls</u>

> Specifications

Type Ruby Surface ColourFlow, Indoor surface mounted

Colour Black or white

Material Powder coated aluminium

Weight 3698 gram

Optics 16° | 49° | 63°

Light source CLS Dynamic Colour Chip

RGB-W 3000K | RGB-W 4000K | RGB-A

1800K-4000K | 2700K-6500K

Power consumption Max. 45 - 90 Watt Power supply $80 \sim 264$ VAC

Driver Driver included | Driver internal

Dimming DMX512 | DMX Analog dimmable | DMX Hybrid dimmable | PWM dimmable

Connection Open end

IP rating IP 20
Protection class 1
Certifications CE
Energy label A

Lifetime 50000 hours



LB Value L90B10 at 50.000h

Warranty 5 years

Accessories Remarks Reflector available in several different beam angles and a honeycomb louvre Fitted with a 5 core DMX combi cable

