

## **EMERALD L**



The Emerald L downlighter is a versatile and energy-efficient lighting fixture that is perfect for a variety of applications. With a large beam angle and a choice of different wattages, it is easy to find the right lighting for your needs. The different colour temperatures and CRI values mean that you can perfectly configure the lighting for your space.

Categories: Emerald Series, Indoor, Downlighter, Hotels and Restaurants, Offices, Retail

## > Specifications

Type Emerald L, Downlighter

Colour Black or white

Material Plastic (PC\_ABS V0), anodized aluminium

Swivel 360° horizontal

Mounting hole 21-25

Installation depth 180mm (4~6 serie) or 205mm (7-serie)

Optics 70° | 83°

Light source High Power LED
Light output 1600 - 4000 lumen

CRI ~90

2500K | 2700K | 3000K | 3500K | 4000K LED colours

D2W 1800K-3000K

Power consumption Max. 15 - 36 Watt
Drive current 350mA~900 mA

Driver Driver included | Driver external

Dimming Mains dimmable | DALI | Casambi | DMX512

Connection Smart Connect system

Cable length 150 cm

IP rating IP 40
Protection class 3
Certifications CE



 Lifetime
 50.000 hours

 LB Value
 L90B10 at 50.000h

 Warranty
 5 years

Remarks Highly efficient, very low glare convex lens



