

## EMERALD M



The Emerald downlighter is available in 4 different wattages, 5 different colour temperatures, and with different CRI values, so you can find the perfect fixture for your needs. And because all dimming methods are compatible with the Emerald downlighter, you'll have complete control over your lighting at all times.


**Categories:** [Emerald Series](#), [Indoor](#), [Downlighter](#), [Automotive Showrooms](#), [Offices](#), [Retail](#)

## &gt; Specifications


Type	Emerald M, Downlighter
Colour	White or Black
Material	Plastic PC_ABS V0, Anodized aluminium
Mounting hole	14 ~ 20 cm
Installation depth	71mm (4 serie), 106mm (5&6 serie) or 131mm (7 serie)
Optics	70°   83°
Light source	High Power LED
Light output	1600 - 4000 lumen
CRI	>90
LED colours	2500K   2700K   3000K   3500K   4000K D2W 1800K-3000K
Power consumption	Max. 15 - 41 Watt
Drive current	350mA-1000 mA
Driver	Driver included   Driver external
Dimming	Mains dimmable   DALI   Casambi   DMX512
Connection	CLS Smart Connect System
Cable length	150
IP rating	IP 40
Protection class	3
Certifications	CE

Lifetime Warranty	50.000 hour 5 years
Remarks	Innovative convex lens application that generates a unmatched light efficiency in combination with a very low glare

4 serie



5 & 6 serie



7 serie

