


EMERALD M



The Emerald downlighter is available in 4 different wattages, 5 different colour temperatures, and with different CRI values, so you can find the perfect fixture for your needs. And because all dimming methods are compatible with the Emerald downlighter, you'll have complete control over your lighting at all times.

Categories: [Emerald Series](#), [Indoor](#), [Downlighter](#), [Automotive Showrooms](#), [Offices](#), [Retail](#)


> Specifications

Type	Emerald M, Downlighter
Colour	White or Black
Material	Plastic PC_ABS V0, Anodized aluminium
Mounting hole	15 ~ 20 cm
Installation depth	165mm (4~6 serie) or 190mm (7 serie)
Optics	70° 83°
Light source	High Power LED
Light output	1600 - 4000 lumen
CRI	~90
LED colours	2500K 2700K 3000K 3500K 4000K D2W 1800K-3000K
Power consumption	Max. 15 - 36 Watt
Drive current	350mA ~ 900mA
Driver	Driver included Driver external
Dimming	Mains dim DALI Casambi DMX512
Connection	CLS Smart Connect System
Cable length	150
IP rating	IP 40
Protection class	3
Certifications	CE

Lifetime	50.000 hour
LB Value	L90B10 at 50.000h
Warranty	5 years

Remarks	Innovative convex lens application that generates a unmatched light efficiency in combination with a very low glare
---------	---------------------------------------------------------------------------------------------------------------------

4, 5 & 6 serie



7 serie

