

FLORENCE GIII



The Florence GIII is a 3 watt tiltable LED downlighter with superior light output and an ultra-compact design. Its black aluminium finish and CNC cut massive aluminium housing make it the perfect choice for any application requiring optimal heat dissipation. A wide range of dimming methods is available, including DMX512, DALI and Casambi.

Categories: [Florence GIII Series](#), [Indoor](#), [Downlighter](#), [Hotels and Restaurants](#), [Museums & Galleries](#), [Offices](#)

> Specifications

| | |
|--------------------|-------------------------------------|
| Type | Florence GIII, Downlighter |
| Colour | Black |
| Material | Coated aluminum |
| Weight | 75 gram |
| Swivel | 360° horizontal 50° vertical |
| Mounting hole | 5 cm |
| Installation depth | 5 cm |
| <hr/> | |
| Optics | 15° 40° |
| Light source | High Power LED |
| Light output | 200 lumen |
| CRI | 90 |
| LED colours | 2700K 3000K 4000K |
| <hr/> | |
| Power consumption | Max. 3 Watt |
| Drive current | 700mA |
| Driver | Driver excluded Driver external |
| Dimming | mains 1-10 dali casambi dmx |
| Connection | CLS Smart connect system |
| Cable length | 100 cm |
| <hr/> | |
| IP rating | IP 40 |
| Protection class | 3 |
| Certifications | CE |

| | |
|--------------|------------------------------|
| Energy label | A |
| Lifetime | 50000 hours |
| LB Value | L90B10 at 50.000h |
| Warranty | 5 years |
| Remarks | Extreme compact measurements |

