

FLORENCE GIII BRACKET



The Florence GIII bracket lighting fixture is a sleek and stylish surface-mounted LED light that is perfect for a variety of applications. This light is perfect for replacing 20 watt halogen lamps with a high quality LED fixture in all sorts of settings. Additionally, the Florence GIII bracket lighting fixture features interchangeable optics, so you can easily customize the light output to your needs.

Categories: [Product Series](#), [Florence GIII Series](#), [Indoor](#), [Surface mounted](#), [Architainment](#), [Museums & Galleries](#), [Theatres & Concert halls](#)

> Specifications

Type	Florence GIII Bracket, Indoor surface mounted
Colour	Black
Material	Anodized massive aluminum CNC cut heat sink
Weight	45 gram
Swivel	360° horizontal 270° vertical
Installation depth	5
Optics	15° 40°
Light source	High power LED
Light output	200 lumen
CRI	90
LED colours	2700K 3000K 4000K
Power consumption	Max. 3 Watt
Drive current	700
Driver	Driver excluded Driver external
Dimming	Mains dimmable 1-10V dimmable DALI Casambi DMX512
Cable length	150 cm
IP rating	IP 40
Protection class	3
Energy label	A

Lifetime	50000 hours
LB Value	L90B10 at 50.000h
Warranty	5 years

Remarks	Extreme compact measurements. 15° lens included
---------	---

