

FOCUS MICRO G2



The most compact, but fully equipped, zoom fixture available. Standing upright, the Focus Micro G2 is only 48 mm to 66 mm high. With a diameter of 16 mm, the Focus Micro G2 is about the size of an AA battery. The design makes the Focus Micro G2 virtually invisible and unobtrusive, without compromising on functionality. Besides the zoom range of no less than 6° to 90°, some key features are high-quality LED light sources with a Colour Rendering Index of ~95 and a choice of four different colour temperatures and control methods.

Categories: [Focus Micro Series](#), [Indoor](#), [Surface mounted](#), [Museums & Galleries](#)

> Specifications

Type	Focus Micro G2, Indoor surface mounted
Colour	Black or white
Material	Coated aluminium
Weight	20 gram
Swivel	360° horizontal 90° vertical

Optics	6°-90°
Light source	High Power
Light output	87 lumen
CRI	~95
LED colours	2700K 3000K 3500K 4000K

Power consumption	Max. 1 Watt
Drive current	350mA
Driver	Driver excluded Driver external
Dimming	mains 1-10 magno casambi dmx
Connection	CLS Smart Connect system

IP rating	IP 20
Protection class	3
Certifications	CE
Energy label	A

Lifetime	50000 hours
LB Value	L90B10 at 50.000h
Warranty	5 years

Accessories	Magnetic foot mount
Remarks	Internal slot for correction/colour filters, 2 cuttable snoots included.

