# FOCUS MICRO



The most compact, but fully equipped, zoom fixture available. Standing upright, the Focus micro is only 48 mm to 66 mm high. With a diameter of 16 mm, the Focus Micro is about the size of an AA battery. The design makes the Focus Micro virtually invisible and unobtrusive, without compromising on functionality. Besides the zoom range of no less than 6º to 90º, some key features are high quality LED light sources with a Colour Rendering Index of >95 and a choice of four different colour temperatures and control methods.

**Categories:** Focus Micro Series, Indoor, Surface mounted, Museums & Galleries

## > Specifications

| | |
|---|---|
| Type | Focus Micro, Indoor surface mounted |
| Colour | Black or white |
| Material | Coated aluminium |
| Weight | 20 gram |
| Swivel | 360° horizontal \| 90° vertical |

| | |
|---|---|
| Optics | 6º-90º |
| Light source | High Power |
| Light output | 87 lumen |
| CRI | 95 |
| LED colours | 2700K \| 3000K \| 3500K \| 4000K |

| | |
|---|---|
| Power consumption | Max. 1 Watt |
| Drive current | 350mA |
| Driver | Driver excluded \| Driver external |
| Dimming | Mains dimmable \| 1-10V dimmable \| Magno dim \| Casambi \| DMX512 |
| Connection | CLS Smart Connect system |

| | |
|---|---|
| IP rating | IP 20 |
| Protection class | 3 |
| Certifications | CE |
| Energy label | A |

| | |
|---|---|
| Lifetime | 50000 hours |
| Warranty | 5 years |

| | |
|---|---|
| Accessories | Magnetic foot mount |
| Remarks | Internal slot for correction/colour filters, 2 cuttable snoots included. |

