

## RUBY BRACKET MODULAR COLOURFLOW



The Ruby Bracket ColourFlow is a unique lighting fixture that offers versatile possibilities for lighting design. With its high-quality white light and shadow-free colour mixing, it is perfect for general illumination in a variety of spaces. Additionally, its Tunable White LED modules allows you to choose between 1800-4000K and 2700-6500K as standard. These fixtures are easy to set up and use, thanks to the Powercon TRUE in/out power connectors that allow daisy-chaining up to 6 units on a single power outlet.

**Categories:** [Product Series](#), [Ruby Series](#), [Indoor](#), [Surface mounted](#), [ColourFlow](#), [Architainment](#), [Theatres & Concert halls](#)

### > Specifications

Type	Ruby Bracket Modular ColourFlow, Indoor surface mounted
Colour	White or black
Material	Coated aluminium
Weight	3600 gram
Optics	16°   49°   63°
Light source	CLS DCC
LED colours	RGB-W 3000K   RGB-W 4000K   RGB-A 1800K-4000K   2700K-6500K
Power consumption	Max. 45 - 90 Watt
Power supply	80 ~ 264
Driver	Driver included   Driver internal
Dimming	DMX512   DMX Analog dimmable   DMX Hybrid dimmable   PWM dimmable
Connection	Power: Neutrik Powercon TRUE DMX: XLR3
IP rating	IP 20
Protection class	1
Certifications	CE
Energy label	A
Lifetime	50000 hours
LB Value	L90B10 at 50.000h

Warranty 5 years

Accessories Reflectors in several different beam angles and a honeycomb louvre

Remarks Neutrik Powercon TRUE chassis / DMX XLR3 chassis

