

RUBY COMPACT BRACKET



The Ruby Compact Bracket is a surface-mounted LED fixture that delivers a high light output, despite its small form factor. Thanks to its extensive range of light sources and control methods, the configuration possibilities are numerous. With its versatile design, the Ruby Compact Bracket is perfect for a wide variety of applications, from showrooms and shops to reception areas and public spaces in museums and offices.

Categories: [Ruby Compact Series](#), [Indoor](#), [Surface mounted](#), [Architainment](#), [Museums & Galleries](#), [Theatres & Concert halls](#)

> Specifications

Type	Ruby Compact Bracket, Indoor surface mounted
Colour	Black or white
Material	Powder coated aluminium
Weight	1500 gram

Optics	19° 37° 63°
Light source	High Power LED
Light output	2800 lumen
CRI	>90 ~ 98
LED colours	2700K 3000K 3500K 4000K D2W 1800K-3000K

Power consumption	Max. 30 Watt
Power supply	200~240 VAC
Driver	Driver included Driver internal
Dimming	mains 1-10 dali casambi dmx wireless
Connection	Cable with open end
Cable length	200 cm

IP rating	IP 20
Protection class	1
Certifications	CE

Lifetime	50.000 hours
LB Value	L90B10 at 50.000h
Warranty	5 years

Accessories Honey comb

