

REVO COLOURFLOW DMX



The Revo ColourFlow gives you everything that's needed to create atmospheres. This fixture can be managed wirelessly via Casambi or (Wireless) DMX and is available with RGBW, RGBA and AWB LED modules.

Categories: [Revo Series](#), [Outdoor](#), [Surface mounted](#), [ColourFlow](#), [Automotive Showrooms](#), [Offices](#), [Theatres & Concert halls](#)

> Specifications

Type	Revo ColourFlow DMX, IP67 Outdoor surface Fixture
Colour	Blank or black
Material	CNC cut aluminium
Weight	1800 gram
Swivel	360° horizontal 270° vertical
Ambient temperature	-10°C till 40°C

Optics	8° 12° 30° 60° 80° 12 x 46°
Light source	High Power LED
LED colours	RGB-W RGB-A AWB

Power consumption	Max. 20 Watt
Power supply	100~240 VAC
Driver	Driver included Driver internal
Dimming	Casambi DMX512 Wireless DMX
Connection	Cable with open end
Cable length	200 cm

IP rating	IP 67
Protection class	1
Certifications	CE

Lifetime	50.000 hours
LB Value	L90B10 at 50.000h

Warranty

3 years

Technologies

Dynamic Power Control | Dynamic Temperature Control

Accessories

Snoot, wall bracket, ground pin, extension pipe

Remarks

Ventillation gland with Gote-Tex membrane to avoid condensation

