

REVO COLOURFLOW DMX



The Revo ColourFlow gives you everything that's needed to create atmospheres. This fixture can be managed wirelessly via Casambi or (Wireless) DMX and is available with RGBW, RGBA and AWB LED modules.

Categories: Revo Series, Outdoor, Surface mounted, ColourFlow, Automotive Showrooms, Offices, Theatres & Concert halls

> Specifications

Type Revo ColourFlow DMX, IP67 Outdoor surface Fixture

Colour Blank or black
Material CNC cut aluminium

Weight 1800 gram

Swivel 360° horizontal | 270° vertical

Ambient temperature -10°C till 40°C

Optics 8° | 12° | 30° | 60° | 80° | 12 x 46°

Light source High Power LED
LED colours RGB-W | RGB-A | AWB

Power consumption Max. 20 Watt Power supply 100~240 VAC


Driver Driver included | Driver internal
Dimming Casambi | DMX512 | Wireless DMX

Connection Cable with open end

Cable length 200 cm

IP rating IP 67
Protection class 1
Certifications CE

Lifetime 50.000 hours
LB Value L90B10 at 50.000h






Warranty 3 years

Technologies

Accessories Snoot, wall bracket, ground pin, extension pipe

Remarks Ventillation gland with Gote-Tex membrane to avoid condensation



Dynamic Power Control | Dynamic Temperature Control

