

REVO XL COLOURFLOW DMX



The Revo XL ColourFlow DMX is a unique, configurable LED lighting fixture that offers designers new possibilities for creating stunning visuals. This two-section fixture can be controlled separately, allowing for different light colours and beam angles on each side. The durable CNC-cut aluminium housing is IP67 rated for outdoor use, and features a ventilation gland with Gore-Tex membrane to prevent condensation. The interchangeable optics lenses are fast and easy to change, and the 5 core DMX combi cable makes installation a breeze.

Categories: Revo XL Series, Outdoor, Surface mounted, ColourFlow

> Specifications

Type Revo XL ColourFlow DMX, IP67 configurable outdoor surface mounted fixture

Colour Blank or black

Material CNC machined aluminium

Weight 3600 gram

Swivel 360° horizontal | 270° vertical

Ambient temperature -10°C to 40°C

Optics 8° | 12° | 30° | 60° | 80° | 12x46°

Light source High Power LED

CRI >80

RGB-W 3000K | RGB-W 4000K | RGB-A | AWB

1800K-3000K | 1800K-4000K | 2700K-5000K


Power consumption Max. 40 Watt Power supply 100~240 VAC

Driver Driver included | Driver internal
Dimming Casambi | DMX512 | Wireless DMX

Connection Cable with open end

Cable length 200 cm

IP rating IP 67
Protection class 3
Certifications CE





Lifetime 50.000 hours
LB Value L90B10 at 50.000h

Warranty 3 years

Technologies Dynamic Power Control | Dynamic Temperature Control

Accessories Snoot, ground pin, extension pipe

Remarks Ventilation gland with Gore-Tex membrane to avoid condensation. Fitted with a 5 core DMX combi cable

