

## REVO COMPACT INGROUND



The Revo Compact Inground is a configurable and sustainable lighting fixture. With more than 200 different configurations possible, this fixture can be customized to fit any need. The interchangeable lenses make it easy to change the light setting on the job, and the ventilation gland with Gore-Tex membrane prevents condensation build-up. This fixture is also Future-proof; as all parts are easily interchangeable, the Revo Compact Inground will never be outdated.

**Categories:** [Revo Inground Series](#), [Outdoor](#), [Inground](#), [Architainment](#)

### > Specifications

Type	Revo Compact Inground, Outdoor Inground
Colour	Die cast housing + anti corrosion housing: black
Material	Marine grade 316 stainless steel mounting ring. Stainless steel 316 mounting screws. ABS plastic anti corrosion housing. Aluminium die cast housing
Weight	2300 gram
Mounting hole	16,6 cm
Installation depth	19,8 cm
Pressure	15 kg/cm <sup>2</sup>
Ambient temperature	-10°C till 40°C
Optics	8°   12°   30°   61°   12 x 46°
Light source	High Power LED
Light output	800 lumen
CRI	~80
LED colours	2200K   2700K   3000K   4000K   5000K   6500K   amber   blue   red   green   limegreen
Power consumption	Max. 10 Watt
Power supply	100 ~ 240 VAC   24 VDC
Driver	Driver included   Driver internal
Connection	cable with open end
Cable length	200 cm
IK-class	IK10

IP rating	IP 67
Protection class	1
Certifications	CE

---

LB Value	L90B10 at 50.000h
Warranty	3 years

---

Remarks	Ventilation gland with Gore-Tex membrane fitted to avoid moisture and condensation IP 67 2/3/4 way gel mold set included in the package Double IP67 protection.
---------	---

