

REVO INGROUND COLOURFLOW DMX



The Revo ColourFlow offers a great way to create anything from subtle shades and pastel colours to very saturated colours. The Revo comes in many configurations, including RGBW, RGBA and AWB for creating delicate hues that can be difficult with other lighting systems. With this particular type you get an accurate white balance between 1800K all the way up to 8000K!

Categories: [Revo Inground Series](#), [Outdoor](#), [Inground](#), [ColourFlow](#), [Architainment](#), [Hotels and Restaurants](#), [Museums & Galleries](#)

> Specifications

Type	Revo Inground ColourFlow DMX, Outdoor Inground
Colour	Die cast housing + anti corrosion housing: black. Cover ring: stainless steel colour
Material	Marine grade 316 stainless steel mounting ring. Stainless steel 316 mounting screws. ABS plastic anti corrosion housing. Aluminum die cast housing.
Weight	6950 gram
Swivel	50° vertical
Mounting hole	25,5 cm
Installation depth	35,5 cm
Pressure	15 kg/cm ²
Ambient temperature	-10°C till 40°C
Optics	8° 12° 30° 61° 80° 12x46°
Light source	High Power LED
CRI	~80
LED colours	RGB-W 3000K RGB-W 4000K RGB-A AWB
Power consumption	Max. 20 Watt
Power supply	200~277 VAC
Driver	Driver included Driver internal
Dimming	DMX512
Connection	Cable with open end
Cable length	200 cm

IK-class	IK10
IP rating	IP 67
Protection class	3
Certifications	CE
Energy label	A

Lifetime	50.000 hours
LB Value	L90B10 at 50.000h
Warranty	3 years

Remarks Ventilation gland with Gore-Tex membrane fitted to avoid moisture and condensation Fitted with a 5 core DMX combi cable Beam direction adjustable in multiple directions due to solid ball joint Double IP67 protection.

