

REVO INGROUND COLOURFLOW DMX



The Revo ColourFlow offers a great way to create anything from subtle shades and pastel colours to very saturated colours. The Revo comes in many configurations, including RGBW, RGBA and AWB for creating delicate hues that can be difficult with other lighting systems. With this particular type you get an accurate white balance between 1800K all the way up to 8000K!

Categories: Revo Inground Series, Outdoor, Inground, ColourFlow, Architainment, Hotels and Restaurants, Museums & Galleries

> Specifications

Type Revo Inground ColourFlow DMX, Outdoor Inground

Colour Die cast housing + anti corrosion housing: black. Cover ring: stainless steel colour

Marine grade 316 stainless steel mounting ring. Stainless steel 316 mounting screws. ABS plastic anti corrosion

housing. Aluminum die cast housing.

Weight 6950 gram

Swivel 50° vertical

Mounting hole 25,5 cm

Installation depth 35,5 cm

Pressure 15 kg/cm²

Ambient temperature -10°C till 40°C

Optics 8° | 12° | 30° | 61° | 80° | 12x46°

Light source High Power LED

CRI ~80

LED colours RGB-W 3000K | RGB-W 4000K | RGB-A | AWB

Power consumption Max. 20 Watt Power supply 200~277 VAC

Driver Driver included | Driver internal

Dimming DMX512

Connection Cable with open end

Cable length 200 cm



IK-classIK10IP ratingIP 67Protection class3CertificationsCEEnergy labelA

Lifetime 50.000 hours
LB Value L90B10 at 50.000h

Warranty 3 years

Remarks

Ventilation gland with Gore-Tex membrane fitted to avoid moisture and condensation Fitted with a 5 core DMX combi cable Beam direction adjustable in multiple directions due to solid ball joint Double IP67 protection.

