



## **REVO INGROUND DMX**



The Revo Inground lighting fixture is a high-quality, sustainable product that is easy to install and configure. With its IP67 rating, it is perfect for use in any outdoor setting. Easy and precise control via DMX512 makes this fixture a versatile and powerful lighting solution for any installation.

Categories: Revo Inground Series, Outdoor, Inground, Architainment, Hotels and Restaurants, Museums & Galleries

## > Specifications

Type Revo Inground DMX, Outdoor Inground

Colour Die cast housing + anti corrosion housing: black. Cover ring: stainless steel colour

Marine grade 316 stainless steel mounting ring. Stainless steel 316 mounting screws. ABS plastic anti corrosion

housing. Aluminum die cast housing.

Weight 6950 gram

Swivel 50° vertical

Mounting hole 25,5 cm

Installation depth 35,5 cm

Pressure 15 kg/cm²

Ambient temperature -10°C till 40°C

Optics 8° | 12° | 30° | 61° | 80° | 12x46°

Light source High Power LED
Light output 2000 lumen

CRI ~80

LED colours 2200K | 2400K | 2700K | 3000K | 4000K | 5000K | 6500K | amber | blue | red | green | limegreen


Power consumption Max. 20 Watt Power supply 200~277 VAC

Driver Driver included | Driver internal
Dimming Mains dim | Casambi | DMX512

Connection Cable with open end

Cable length 200 cm

IK-class IK10





IP ratingIP 67Protection class3CertificationsCEEnergy labelA

Lifetime 50.000 hours
LB Value L90B10 at 50.000h

Warranty 3 years

Remarks

Ventilation gland with Gore-Tex membrane fitted to avoid moisture and condensation Fitted with a 5 core DMX combi cable Beam direction adjustable in multiple directions due to solid ball joint Double IP67 protection.

