

REVO INGROUND TUNABLE WHITE DMX



The Revo Inground Tunable White DMX lighting fixture is the perfect solution for any outdoor installation. With its IP67 rating, it can withstand harsh conditions and deliver bright light where you need it most with greater precision than ever before! The Tunable White LED technology means that you can adjust the colour temperature of the light output to create any desired effect, whether it be for ambience or function.

Categories: [Revo Inground Series](#), [Outdoor](#), [Inground](#), [ColourFlow](#), [Architainment](#), [Hotels and Restaurants](#), [Museums & Galleries](#)

> Specifications

| | |
|---------------------|---|
| Type | Revo Inground Tunable White DMX, Outdoor Inground |
| Colour | Die cast housing + anti corrosion housing: black. Cover ring: stainless steel colour |
| Material | Marine grade 316 stainless steel mounting ring. Stainless steel 316 mounting screws. ABS plastic anti corrosion housing. Aluminum die cast housing. |
| Weight | 6950 gram |
| Swivel | 50° vertical |
| Mounting hole | 25,5 cm |
| Installation depth | 35,5 cm |
| Pressure | 15 kg/cm ² |
| Ambient temperature | -10°C till 40°C |

| | |
|--------------|---|
| Optics | 8° 12° 30° 61° 80° 12x46° |
| Light source | High Power LED |
| CRI | >80 |
| LED colours | 1800K-3000K 1800K-4000K 2700K-5000K |

| | |
|-------------------|-----------------------------------|
| Power consumption | Max. 20 Watt |
| Power supply | 200~277 VAC |
| Driver | Driver included Driver internal |
| Dimming | DMX512 |
| Connection | Cable with open end |
| Cable length | 200 cm |

| | |
|------------------|-------|
| IK-class | IK10 |
| IP rating | IP 67 |
| Protection class | 3 |
| Certifications | CE |
| Energy label | A |

| | |
|----------|-------------------|
| Lifetime | 50.000 hours |
| LB Value | L90B10 at 50.000h |
| Warranty | 3 years |

Remarks Ventilation gland with Gore-Tex membrane fitted to avoid moisture and condensation Fitted with a 5 core DMX combi cable Beam direction adjustable in multiple directions due to solid ball joint Double IP67 protection.

