

REVO INGROUND



With more than 200 different configurations possible, it's easy to find the perfect lighting setup for your space with this versatile and sustainable outdoor fixture. The interchangeable optics allow you to customize the beam angle depending on the desired effect. Thanks to the Gore-Tex membrane technology, condensation inside the fixture is prevented.

Categories: [Revo Inground Series](#), [Outdoor](#), [Inground](#), [Architainment](#), [Hotels and Restaurants](#), [Museums & Galleries](#)

> Specifications

Type	Revo Inground, Outdoor Inground
Colour	Black. Cover ring: Stainless steel
Material	Marine grade 316 stainless steel mounting ring & mounting screws. ABS plastic anti corrosion housing. Aluminium die cast housing.
Weight	6950 gram
Swivel	50° vertical
Mounting hole	25,5 cm
Installation depth	35,5 cm
Pressure	15 kg/cm ²
Ambient temperature	-10°C till 40°C

Optics	8° 12° 30° 61° 80° 12x46°
Light source	High Power LED
Light output	2000 lumen
CRI	~80
LED colours	2200K 2400K 2700K 3000K 4000K amber blue red green limegreen

Power consumption	Max. 20 Watt
Power supply	200~277 VAC
Driver	Driver included Driver internal
Dimming	mains casambi
Connection	Cable with open end
Cable length	200 cm

IK-class	IK10
IP rating	IP 67
Protection class	3
Certifications	CE
Energy label	A

Lifetime	50.000 hours
LB Value	L90B10 at 50.000h
Warranty	3 years

Remarks Ventilation gland with Gore-Tex membrane to avoid condensation. Beam direction adjustable thanks to a solid ball joint. 2/3/4 way gel mould set included. Double IP67 protection.

