

## REVO INGROUND



With more than 200 different configurations possible, it's easy to find the perfect lighting setup for your space with this versatile and sustainable outdoor fixture. The interchangeable optics allow you to customize the beam angle depending on the desired effect. Thanks to the Gore-Tex membrane technology, condensation inside the fixture is prevented.

**Categories:** [Revo Inground Series](#), [Outdoor](#), [Inground](#), [Architainment](#), [Hotels and Restaurants](#), [Museums & Galleries](#)

### > Specifications

|                     |   |
|---------------------|---|
| Type                | Revo Inground, Outdoor Inground   |
| Colour              | Black. Cover ring: Stainless steel  |
| Material            | Marine grade 316 stainless steel mounting ring & mounting screws. ABS plastic anti corrosion housing. Aluminium die cast housing. |
| Weight              | 6950 gram   |
| Swivel              | 50° vertical  |
| Mounting hole       | 25,5 cm   |
| Installation depth  | 35,5 cm   |
| Pressure            | 15 kg/cm <sup>2</sup>   |
| Ambient temperature | -10°C till 40°C   |

---

|              |  |
|--------------|--|
| Optics       | 8°   12°   30°   61°   80°   12x46°  |
| Light source | High Power LED   |
| Light output | 2000 lumen   |
| CRI          | ~80  |
| LED colours  | 2200K   2400K   2700K   3000K   4000K   amber   blue   red   green   limegreen |

---

|                   |                                   |
|-------------------|-----------------------------------|
| Power consumption | Max. 20 Watt                      |
| Power supply      | 200~277 VAC                       |
| Driver            | Driver included   Driver internal |
| Dimming           | mains   casambi                   |
| Connection        | Cable with open end               |
| Cable length      | 200 cm                            |

---

|                  |       |
|------------------|-------|
| IK-class         | IK10  |
| IP rating        | IP 67 |
| Protection class | 3     |
| Certifications   | CE    |
| Energy label     | A     |

|          |                   |
|----------|-------------------|
| Lifetime | 50.000 hours      |
| LB Value | L90B10 at 50.000h |
| Warranty | 3 years           |

Remarks Ventilation gland with Gore-Tex membrane to avoid condensation. Beam direction adjustable thanks to a solid ball joint. 2/3/4 way gel mould set included. Double IP67 protection.

