

REVO BASIC DMX



The Revo Basic DMX is a 20W, IP67-rated outdoor lighting fixture that features a massive CNC-cut aluminium housing. This fixture is perfect for façade lighting, gardens, landscapes, and other applications where a compact light with high output is desired. With interchangeable optics and lenses, the Revo Basic can be customized to meet the needs of any application. And thanks to its sustainable design, this fixture will never become outdated.

Categories: [Revo Series](#), [Outdoor](#), [Surface mounted](#), [Automotive Showrooms](#), [Offices](#), [Theatres & Concert halls](#)

> Specifications

| | |
|---------------------|--|
| Type | Revo Basic DMX, IP67 Outdoor surface fixture |
| Colour | Blank or Black |
| Material | CNC cut aluminium |
| Weight | 1800 gram |
| Swivel | 360° horizontal 270° vertical |
| Ambient temperature | -10°C till 40°C |

| | |
|--------------|--|
| Optics | 8° 12° 30° 60° 80° 12 x 46° |
| Light source | High Power LED |
| Light output | 2000 lumen |
| CRI | >80 |
| LED colours | 1800K 2200K 2400K 2700K 3000K 4000K 5000K 6500K amber blue red green limegreen |

| | |
|-------------------|-----------------------------------|
| Power consumption | Max. 20 Watt |
| Power supply | 100~240 VAC |
| Driver | Driver included Driver internal |
| Dimming | DMX512 |
| Connection | Cable with open end |
| Cable length | 200 cm |

| | |
|------------------|-------|
| IP rating | IP 67 |
| Protection class | 1 |
| Certifications | CE |

| | |
|----------|-------------------|
| Lifetime | 50.000 hours |
| LB Value | L90B10 at 50.000h |
| Warranty | 3 years |

| | |
|--------------|---|
| Technologies | Dynamic Temperature Control |
| Accessories | Snoot, wall bracket, ground pin, extension pipe |
| Remarks | Ventillation gland with Gote-Tex membrane to avoid condensation |

