

REVO BASIC XL



The Revo Basic XL is a compact, yet powerful, 40 watt outdoor lighting fixture that is perfect for a wide variety of applications. CNC cut from massive aluminium and IP67 rated for protection against the elements. With more than 800 possible configurations, the Revo Basic XL can be tailored to meet your specific needs. And with interchangeable optics and the configurable dimming capabilities, you can always get the perfect light setting for the job.

Categories: Revo XL Series, Outdoor, Surface mounted

> Specifications

Type Revo Basic XL, IP67 outdoor surface mounted fixture

Colour Blank or Black

Material CNC machined aluminium

Weight 3600 gram

Swivel 360° horizontal | 270° vertical

Ambient temperature -10°C to 40°C

Optics 8° | 12° | 30° | 60° | 80° | 12x46°

Light source High Power LED
Light output 3200 lumen
CRI >80

LED colours 2200K | 2400K | 2700K | 3000K | 4000K | 5000K | 6500K | amber | blue | red | green | limegreen

Power consumption Max. 40 Watt
Power supply 100~240 VAC

Driver Driver included | Driver internal
Dimming Mains dimmable | Magno dim | DALI

Connection Cable with open end

Cable length 200 cm

IP rating IP 67
Protection class 3
Certifications CE

Product: Revo Basic XL Generated: October 23, 2025



Lifetime 50.000 hours
LB Value L90B10 at 50.000h

Warranty 3 years

Accessories Snoot, ground pin, extension pipe

Remarks Ventilation gland with Gore-Tex membrane to avoid condensation. Fitted with a 5 core DMX combi cable

















