

REVO BASIC XL



The Revo Basic XL is a compact, yet powerful, 40 watt outdoor lighting fixture that is perfect for a wide variety of applications. CNC cut from massive aluminium and IP67 rated for protection against the elements. With more than 800 possible configurations, the Revo Basic XL can be tailored to meet your specific needs. And with interchangeable optics and the configurable dimming capabilities, you can always get the perfect light setting for the job.

Categories: [Revo XL Series](#), [Outdoor](#), [Surface mounted](#)

> Specifications

| | |
|---------------------|---|
| Type | Revo Basic XL, IP67 outdoor surface mounted fixture |
| Colour | Blank or Black |
| Material | CNC machined aluminium |
| Weight | 3600 gram |
| Swivel | 360° horizontal 270° vertical |
| Ambient temperature | -10°C to 40°C |

| | |
|--------------|--|
| Optics | 8° 12° 30° 60° 80° 12x46° |
| Light source | High Power LED |
| Light output | 3200 lumen |
| CRI | >80 |
| LED colours | 2200K 2400K 2700K 3000K 4000K 5000K 6500K amber blue red green limegreen |

| | |
|-------------------|-----------------------------------|
| Power consumption | Max. 40 Watt |
| Power supply | 100~240 VAC |
| Driver | Driver included Driver internal |
| Dimming | Mains dimmable Magno dim DALI |
| Connection | Cable with open end |
| Cable length | 200 cm |

| | |
|------------------|-------|
| IP rating | IP 67 |
| Protection class | 3 |
| Certifications | CE |

| | |
|----------|-------------------|
| Lifetime | 50.000 hours |
| LB Value | L90B10 at 50.000h |
| Warranty | 3 years |

| | |
|-------------|--|
| Accessories | Snoot, ground pin, extension pipe |
| Remarks | Ventilation gland with Gore-Tex membrane to avoid condensation. Fitted with a 5 core DMX combi cable |



