

REVO BASIC



The Revo Basic is a 20W, IP67-rated outdoor lighting fixture that features a massive CNC-cut aluminium housing and configurable options. This fixture is perfect for façade lighting, gardens, landscapes, and other applications where a compact light with high output is desired. With interchangeable optics and lenses, the REVO Basic can be customized to meet the needs of any application. And thanks to its sustainable design, this fixture will never become outdated.

Categories: [Revo Series](#), [Outdoor](#), [Surface mounted](#), [Automotive Showrooms](#), [Offices](#), [Theatres & Concert halls](#)

> Specifications

Type	Revo Basic, IP67 Outdoor surface fixture
Colour	Blank or black
Material	CNC cut aluminium
Weight	1800 gram
Swivel	360° horizontal 270° vertical
Ambient temperature	-10°C till 40°C

Optics	8° 12° 30° 60° 80° 12 x 46°
Light source	High Power LED
Light output	2000 lumen
CRI	>80
LED colours	1800K 2200K 2400K 2700K 3000K 4000K 5000K 6500K amber blue red green limegreen

Power consumption	Max. 20 Watt
Power supply	100~240 VAC
Driver	Driver included Driver internal
Dimming	DALI
Connection	Cable with open end
Cable length	200 cm

IP rating	IP 67
Protection class	1
Certifications	CE

Lifetime	50.000 hours
LB Value	L90B10 at 50.000h
Warranty	3 years

Accessories	Shoot, ground pin, extension pipe
Remarks	Ventillation gland with Gote-Tex membrane to avoid condensation

